



PART NUMBER:	DATE:
PROJECT #:	TYPE:
PREPARED BY:	

## RESIDENTIAL GRADE FIRE CAULK TECHNICAL DATA SHEET

### PRODUCT DESCRIPTION

F4P Fireblock-X is a noncombustible caulking compound used to fill the annular space around vents, pipes, ducts, cables and wires at ceiling and floor level in non-rated one and two-family residential construction. Fireblock-X is designed to seal penetrations to resume the integrity of fire blocks within concealed stud wall cavities and prevent the free passage of draft, flame, smoke, and toxic gases.



### SPECIFICATIONS

- **Application:** Type V residential construction.
- **Color:** Brick Red
- **Size:** 10.3 Caulk Tube
- **Tack Free Time:** 10 min. at 75°F
- **Cure Time:** 48-72 hours at 75°F

### CERTIFICATIONS

Tested to ASTM-E814 (UL 1479) and ATSM-E1966 (UL-2079)\*

### ORDERING INFORMATION

PART NUMBER	STOCK CODE
F4P FIRE BLOCK	0250-8648

### RESOURCES

MSDS/EDS/PRODUCT DATA SHEETS: [f4p-usa.com](http://f4p-usa.com)      CUSTOMER SERVICE: 772-408-5211

### DISCLAIMER

Recommendations for use of this product are based on tests we believe to be reliable. Manufacturer and seller are not responsible for results where this product is used under conditions beyond our control. If when applied as directed, this material peels, cracks or separates, it will be replaced without charge upon presentation of proof of purchase and used cartridge. This limited warranty only applies to residential use and damages including consequential damage and other remedies. No other warranties apply, including fitness for a particular purpose.