



PART NUMBER:	DATE:
PROJECT #:	TYPE:
PREPARED BY:	

FIRESTOP SEALANT TECHNICAL DATA SHEET

PRODUCT DESCRIPTION

F4P Firestop 814+ intumescent elastomeric firestopping caulk is a UL Classified, commercial grade sealant designed to resume the integrity up to 4 hour fire rated floors and walls when penetrated by plumbing, electrical, and other mechanical items.



SPECIFICATIONS

- **Color:** Brick Red
- **Size:** 10.3 Caulk Tube
- **Tack Free Time:** 10 min. at 75°F
- **Cure Time:** 48-72 hours at 75°F

CERTIFICATIONS

UL Reference Number 1479

ATSM Tested to ASTM-E814 (UL 1479) and ATSM-E1966 (UL 2079)*

ORDERING INFORMATION

PART NUMBER	STOCK CODE
F4P FIRESTOP 814+	0214-6959

RESOURCES

MSDS/EDS/PRODUCT DATA SHEETS: f4p-usa.com

CUSTOMER SERVICE: 772-408-5211

DISCLAIMER

Recommendations for use of this product are based on tests we believe to be reliable. Manufacturer and seller are not responsible for results where this product is used under conditions beyond our control. If when applied as directed, this material peels, cracks or separates, it will be replaced without charge upon presentation of proof of purchase and used cartridge. This limited warranty only applies to residential use and damages including consequential damage and other remedies. No other warranties apply, including fitness for a particular purpose.