



PART NUMBER:	DATE:
PROJECT #:	TYPE:
PREPARED BY:	

SPLICE REDUCER TECHNICAL DATA SHEET

PRODUCT DESCRIPTION

A compression connector for joining two cables of different sizes.



FEATURES

- High strength
- Plated for low contact resistance
- Corrosion resister
- Environmental Conditions - Non-hazardous

SPECIFICATIONS

PART NUMBER	SIZE	MATERIAL	FINISH	VOLTAGE RATING	TEMPERATURE RATING
F4P SR 2-14	2-14	Alluminium	Tin Plating	600 Volt	90°C
F4P SR 1/0-14	1/0-14	Alluminium	Tin Plating	600 Volt	90°C
F4P SR 4/0-6	4/0-6	Alluminium	Tin Plating	600 Volt	90°C
F4P SR 250-6L	250-6L	Alluminium	Tin Plating	600 Volt	90°C
F4P SR 350-6L	350-6L	Alluminium	Tin Plating	600 Volt	90°C
F4P SR 500-4L	500-4L	Alluminium	Tin Plating	600 Volt	90°C
F4P SR 750-250L	750-250L	Alluminium	Tin Plating	600 Volt	90°C



PART NUMBER:	DATE:
PROJECT #:	TYPE:
PREPARED BY:	

ORDERING INFORMATION

PART NUMBER	STOCK CODE	DESCRIPTION	PACKAGE QTY
F4P SR 2-14	0583-6263	2-14 SPLICE REDUCER	94
F4P SR 1/0-14	0583-6266	1/0-14 SPLICE REDUCER	50
F4P SR 4/0-6	0583-6269	4/0-6 SPLICE REDUCER	38
F4P SR 250-6L	0583-6272	250-6 SPLICE REDUCER LONG	15
F4P SR 350-6L	0583-6275	350-6 SPLICE REDUCER LONG	4
F4P SR 500-4L	0583-6278	500-4 SPLICE REDUCER LONG	5
F4P SR 750-250L	0583-6281	750-250 SPLICE REDUCER LONG	3

RESOURCES

MSDS/EDS/PRODUCT DATA SHEETS: f4p-usa.com

CUSTOMER SERVICE: 772-878-4944

DISCLAIMER

Recommendations for use of this product are based on tests we believe to be reliable. Manufacturer and seller are not responsible for results where this product is used under conditions beyond our control. If when applied as directed, this material peels, cracks or separates, it will be replaced without charge upon presentation of proof of purchase and used cartridge. This limited warranty only applies to residential use and damages including consequential damage and other remedies. No other warranties apply, including fitness for a particular purpose.